



## VIVITAR 2800 AUTOMATIC FLASH



- ▶ Auto Thyristor™ circuitry for faster recycle time and longer battery life.
- ▶ Bounce head from 0-90° for soft even lighting.
- ▶ 2 Automatic ranges for coverage up to 40 feet.
- ▶ Delivers 450-3000 flashes per set of 4 AA alkaline batteries. Recycles in .5-5 seconds.
- ▶ Auto check feature confirms correct exposure in advance of taking the picture.
- ▶ Auto off circuitry turns unit off when not in use.
- ▶ Wide Angle/Colored Filter Kit included. Lens coverage to 35mm plus red, green, and yellow filters.

### SPECIFICATIONS

#### ▶ FLASH

Guide Number	Standard	With Wide Angle Panel		
ISO 100/21°	80	56		
DIN 21	24	17		
Angle of Coverage (35mm Camera)	50mm	35mm		
Flash Duration	1/750 to 1/30,000 of a second			
Angle of Illumination	Standard	With Wide Angle Panel		
	(50mm)	(35mm)		
Vertical	34°	45°		
Horizontal	46°	60°		
Automatic F/Stops and Ranges	Standard	With 28mm Wide Angle Panel		
	(50mm)	(35mm)		
	1/2	1/4	1/2	1/4
ISO 100/21°	6-40 ft.	3-20 ft.	45-28 ft.	3-14 ft.
DIN 21	18-12.2m	9-6.1m	14-8.5m	9-4.3m
Power Source	4 AA Alkaline batteries			
Auto Check	Yes			
Auto Off	Yes			
Recycle Time	0.5-5 seconds			
Number of Flashes	450-3000			
Circuitry	Auto Thyristor™			
Bounce Flash (Vertical)	0°, 45°, 60°, 75°, and 90°			
Open Flash	Yes			
Weight Without Batteries	6 oz. (152g)			

Number of flashes depends on subject distance, reflectivity and auto aperture selected.  
Specifications subject to change without notice. Copyright 1980 Vivitar Corporation.

#### ▶ STOCK NUMBER

231556

# Vivitar

